

abit Engineered

- Press Center
- BIOS Guide
- CPU support
- Download
- BIOS
- Drivers
- Utilities
- Manuals
- FAQs
- Awards
- Contact
- Abroad
- R&D
- Customer Service
- Copyright info
- HOME
- Newsletter Sign-Up
- Please enter a valid
- Subscribe/ Unsubscribe
- Search
- Go
- Product
- FAQs
- News
- Award

MOTHERBOARD Socket 478

Browse by processor

-- Select One --

IS-10 e



Intel 865G Chipset Pentium4 Main board
Supports Prescott CPU
FSB800, DDR400, SATA 150

Product Information

- [Overview](#)
- [Specifications](#)
- [Test Reports](#)

Support Information

- [FAQs](#)
- [BIOS](#)
- [Driver](#)
- [Utility](#)
- [Manual](#)

Specifications

>> CPU

- Supports Intel Pentium 4 Socket 478 processors with 800/533/400MHz FSB (Northwood - v1.0; Northwood and Prescott - v2.0)
- Supports Intel Hyper-Threading Technology

>> Chipset

- Intel 865G / ICH5
- Integrated Intel Extreme Graphics 2
- Supports Advanced Configuration and Power Management Interface (ACPI)

>> Memory

- Two 184-pin DIMM sockets
- Supports 2 DIMM Single / Dual Channel DDR 400/ 333/ 266 memory (Max. 2GB)

>> AGP

- Integrated Intel Extreme Graphics 2
- Accelerated Graphics Port connector supports AGP 8X/4X (0.8V/1.5V)

>> SATA 150

- 2 channel Serial ATA 150MB/s data transfer rate

>> Audio

- 6-Channel AC 97 CODEC on board
- Professional digital audio interface supports optical S/PDIF Output

>> System BIOS

- Supports Plug-and-Play (PNP)
- Supports Advanced Configuration Power Interface (ACPI)
- Supports Desktop Management Interface (DMI)
- Write-Protect Anti-Virus function by AWARD BIOS

>> LAN

- On board 10/100Mb LAN

>> Internal I/O Connectors

- 3 x PCI slots
- 1 x AGP slot
- 1 x Floppy Port supports up to 2.88MB
- 2 x Ultra DMA 33/66/100 Connectors
- 2 x Serial ATA 150 Connectors
- 2 x USB 2.0 headers (Each header support two USB 2.0 devices)
- 1 x CD-IN, 1 x AUX-IN
- 1 x FP-Audio header

>> Back Panel I/O

- 1 x PS/2 Keyboard, 1 x PS/2 mouse
- 1 x Parallel Port, 1 x Serial port
- 1 x VGA Port
- 1 x Audio connectors (S/PDIF Out, Surround Out, Center/Sub, Lin-out, Line-in, Mic)
- 4 x USB 2.0, 1 x RJ-45 LAN Connector

>> **Miscellaneous**

- Micro ATX form factor (244mm*234mm)
- Hardware monitoring – Including Fan speeds, Voltages, System environment temperature

Copyright© 2006 Universal ABIT Co., Ltd. All rights reserved.
Reproduction and distribution in any form without permission is strictly prohibited.
The **abit** logo is a registered trademark of **abit**.