

abit Engineered


- Press Center
- BIOS Guide
- CPU support
- Download
- BIOS
- Drivers
- Utilities
- Manuals
- FAQs
- Awards
- Contact Us
- Abilit
- R&D
- Customer Service
- Copyright info
- HOME
- Newsletter Sign-Up
- Please enter a valid
- Subscribe/ Unsubscribe
- Search
- Go
- Product
- FAQs
- News
- Award

MOTHERBOARD Socket 478

Browse by processor

-- Select One --

IS7-E



Intel 865PE Chipset Pentium 4 Mainboard
DUAL DDR 400, AGP 8X, USB 2.0
SoftMenu™ Technology

Product Information

- [Overview](#)
- [Specifications](#)
- [Awards](#)
- [Test Reports](#)

Support Information

- [FAQs](#)
- [BIOS](#)
- [Driver](#)
- [Utility](#)
- [Manual](#)

Specifications

>> CPU

- Supports Intel Pentium 4 Socket 478 processors(Prescott and Northwood) with 800/533/400 MHz FSB
- Supports Intel Hyper-Threading Technology

>> Chipset

- Intel 865PE / ICH5
- Supports Dual Channel DDR 400 Memory
- Supports Advanced Configuration and Power Management Interface (ACPI)

>> Memory

- Four 184-pin DIMM sockets
- Supports 4 DIMM Single/Dual Channel DDR 400 memory (Max. 4GB)

>> AGP

- Accelerated Graphics Port connector supports AGP 8X/4X (0.8V/1.5V)

>> SATA

- On board 2 channels Serial ATA 150MB/s data transfer rate

>> LAN

- On board 10/100Mb LAN

>> USB 2.0

- 8 ports USB 2.0 Supports 480 Mb/s data transfer rate

>> Audio

- 6-Channel AC 97 CODEC on board
- Professional digital audio interface supports S/P DIF optical In / Out

>> System BIOS

- SoftMenu™ Technology to set CPU parameters
- Supports Plug-and-Play (PNP)
- Supports Advanced Configuration Power Interface (ACPI)
- Write-Protect Anti-Virus function by AWARD BIOS

>> Internal I/O Connectors

- 1 x AGP, 5 x PCI slots
- 1 x IrDA
- 1 x Floppy Port supports up to 2.88MB
- 2 x Ultra DMA 33/66/100 Connectors
- 4 x Serial ATA 150 Connectors (2 x Optional)
- 2 x USB 2.0 headers
- 1 x CD-IN, 1 x AUX-IN

>> Back Panel I/O

- 1 x PS/2 Keyboard, 1 x PS/2 mouse
- 1 x Printer Port, 1 x COM port
- 1 x S/PDIF In connector, 1 x S/PDIF Out connector
- 1 x Audio connector (Front Speaker, Line-in, Mic-in)
- 1 x Audio connector (Center/Sub, Surround Speaker)
- 2 x USB 2.0
- 2 x USB 2.0, 1 x RJ-45 LAN Connector

>> **Miscellaneous**

- ATX form factor
- Hardware Monitoring- Including Fan speed, Voltages, CPU and System temperature

Total Rows:1 Page:1/1

Model	Logo	Media	Country	Award	Date
IS7-E		OCWorkbench	Singapore	Reader's Choice	2004/01/15

Copyright© 2006 Universal ABIT Co., Ltd. All rights reserved.
Reproduction and distribution in any form without permission is strictly prohibited.
The abit logo is a registered trademark of abit.