

abit Engineered™


- Press Center
- BIOS Guide
- CPU support
- Downloads
- BIOS
- Drivers
- Utilities
- Manuals
- FAQs
- Awards
- Contact Us
- Abroad
- R&D
- Customer Service
- Copyright info
- HOME
- Newsletter Sign-Up
- Please enter a valid
- Subscribe/ Unsubscribe
- Search
- Product
- FAQs
- News
- Award

MOTHERBOARD Socket 478

Browse by processor

-- Select One -- ▾

IS7-G e



Intel 865PE Chipset Pentium4 Mainboard
Dual SATA RAID, DUAL DDR400, AGP8X, USB 2.0
SoftMenu™ Technology

Product Information

- [Overview](#)
- [Specifications](#)
- [News](#)
- [Awards](#)
- [Test Reports](#)

Specifications

- CPU**
- Supports Intel Pentium4 Socket 478 processors(Prescott and Northwood) with 800/533/400 MHz FSB
 - Supports Intel Hyper-Threading Technology
- Chipset**
- Intel 865PE/ ICH6-R
 - Supports Dual Channel DDR400 Memory
 - Supports Advanced Configuration and Power Management Interface (ACPI)
- Memory**
- Four 184-pin DIMM sockets
 - Supports 4 DIMM Single/Dual Channel DDR400 memory (Max. 4GB)
- AGP**
- Accelerated Graphics Port connector supports AGP8X/4X (0.8V/1.5V)
- Dual SATA RAID**
- 2 channels Serial ATA 150MB/s data transfer rate via Silicon Image PCI controller
 - Supports RAID 0 or RAID 1
- SATA RAID**
- On board 2 channels Serial ATA 150MB/s data transfer rate
 - Supports RAID 0
- Gigabit LAN**
- On board 10/100/1000Mb LAN
- IEEE 1394**
- Supports IEEE 1394a at 100/200/400 Mb/s transfer rate
- USB 2.0**
- 8 ports USB 2.0 Supports 480 Mb/s data transfer rate
- Audio**
- 6-Channel AC97 CODEC on board
 - Professional digital audio interface supports S/PDIF optical In / Out
- Media XP (Optional)**
- Supports card reader function for Memory Stick™, Secure Digital™ and Type I/II CompactFlash™
 - Supports Wireless Remote Control and S/PDIF Out / Mic In / Headphone Out / USB 2.0 / IEEE 1394
- System BIOS**
- SoftMenu™ Technology to set CPU parameters
 - Supports Plug-and-Play (PNP)
 - Supports Advanced Configuration Power Interface (ACPI)
 - Write-Protect Anti-Virus function by AWARD BIOS
- Internal I/O Connectors**
- 1 x AGP, 5 x PCI slots
 - 1 x IrDA
 - 1 x Floppy Port supports up to 2.88MB
 - 2 x Ultra DMA 33/66/100 Connectors
 - 4 x Serial ATA 150 Connectors (2 x Optional)
 - 2 x USB 2.0 headers, 2 x IEEE 1394a header (Optional)
 - 1 x CD-IN, 1 x AUX-IN
- Back Panel I/O**
- 1 x PS/2 Keyboard, 1 x PS/2 mouse
 - 1 x Printer Port, 1 x COM port
 - 1 x S/PDIF In connector, 1 x S/PDIF Out connector
 - 1 x Audio connector (Front Speaker, Line-in, Mc-in)

Support Information

- [FAQs](#)
- [BIOS](#)
- [Driver](#)
- [Utility](#)
- [Manual](#)

- 1 x Audio connector (Center/Sub, Surround Speaker)
- 2 x USB 2.0, 1 x IEEE 1394a (Optional)
- 2 x USB 2.0, 1 x RJ-45 LAN Connector

Miscellaneous

- ATX form factor
- Hardware Monitoring - Including Fan speed, Voltages, CPU and System temperature

Total Rows:9 Page:1/1

Model	Logo	Media	Country	Award	Date
IS7-G		PC Direkt	Germany	"sehr gut"	2004/06/20
IS7-G		Nexus Hardware	USA	Editor's Choice	2003/08/11
IS7-G		Overclockers	Australia	"Outstanding Overclocking"	2003/07/09
IS7-G		HardwareLuxx	Germany	Unser Favorit	2003/07/04
IS7-G		3D Gameman	Canada	KickAss Award	2003/06/24
IS7-G		Lost Circuits	USA	"A great board"	2003/06/24
IS7-G		HardOCP	USA	Top Pick	2003/06/13
IS7-G		OC Workbench	USA	Gold Award	2003/06/13
IS7-G		PC Praxis	Germany	Preistipp	2003/06/03

Copyright© 2006 Universal ABIT Co., Ltd. All rights reserved.
 Reproduction and distribution in any form without permission is strictly prohibited.
 The abit logo is a registered trademark of abit.