


abit Engineered™

- Press Center
- BIOS Guide
- CPU support
- Downloads
- BIOS
- Drivers
- Utilities
- Manuals
- FAQs
- Awards
- Contact Us
- Abilit
- R&D
- Customer Service
- Copyright info
- HOME
- Newsletter Sign-Up
- Please enter a valid
- Subscribe/ Unsubscribe
- Search
- Go
- Product
- FAQs
- News
- Award

MOTHERBOARD Socket 478

Browse by processor
-- Select One --

MS7-Ve



Intel 848P Chipset Pentium 4 Mainboard
SATA, DDR 400, AGP 8X, USB 2.0
SoftMenu™ Technology

Product Information

- [Specifications](#)
- [Test Reports](#)

Support Information

- [FAQs](#)
- [BIOS](#)
- [Driver](#)
- [Utility](#)

Specifications

- >> CPU**
- Supports Intel Pentium 4 Socket 478 processors with 800/533/400 MHz Front Side Bus
 - Supports Intel Hyper-Threading Technology

- >> Chipset**
- Intel 848P / ICH5
 - Supports Single Channel DDR 400/333 Memory
 - Supports Advanced Configuration and Power Management Interface (ACPI) ([Winbond W83303D](#))

- >> Memory**
- Two 184-pin DIMM sockets
 - Supports 2 DIMM Single Channel DDR 400/333 memory (Max. 2GB)

- >> AGP**
- Accelerated Graphics Port connector supports AGP 8X/4X (0.8V/1.5V)

- >> Serial ATA**
- 2 channels Serial ATA 150MB/s data transfer rate

- >> LAN**
- On board 10/100Mb LAN (Realtek RTL8101L)

- >> USB 2.0**
- 8 ports USB 2.0 Supports 480 Mb/s data transfer rate

- >> Audio**
- 6-Channel AC 97 CODEC on board (Realtek ALC650)
 - Professional digital audio interface supports 24-bit S/PDIF Output

- >> ABIT Engineered**
- ABIT SoftMenu™ Technology
 - ABIT CPU ThermalGuard™
 - ABIT FlashMenu™
 - ABIT TweakGuard™
 - ABIT FanSecure™

- >> Internal I/O Connectors**
- 1 x AGP, 5 x PCI slots
 - 1 x Floppy Port supports up to 2.88MB
 - 2 x Ultra DMA 33/66/100 Connectors
 - 2 x Serial ATA 150 Connectors
 - 2 x USB 2.0 headers
 - 1 x CD-IN, 1 x AUX-IN

- >> Back Panel I/O**
- 1 x PS/2 Keyboard, 1 x PS/2 mouse
 - 1 x Printer Port, 1 x COM port
 - 1 x S/PDIF Out connector
 - 1 x Audio connector (Front Speaker, Line-in, Mic-in)
 - 1 x Audio connector (Center/Sub, Surround Speaker)

- 2 x USB 2.0
- 2 x USB 2.0, 1 x RJ-45 LAN Connector

>> **Miscellaneous**

- ATX form factor
- Hardware Monitoring – Including Fan speed, Voltages, CPU and System temperature

Copyright© 2006 Universal ABIT Co., Ltd. All rights reserved.
Reproduction and distribution in any form without permission is strictly prohibited.
The **abit** logo is a registered trademark of **abit**.