

abit Engineered™


- | Press Center
- | BIOS Guide
- | CPU support
- | Downloads
- BIOS
- Drivers
- Utilities
- Manuals
- | FAQs
- | Awards
- | Contact Us
- | About Us
- R&D
- Customer Service
- Copyright info
- | HOME
- Newsletter Sign-Up
-
- Subscribe / Unsubscribe
- Search
- Product
- FAQs
- News
- Award

MOTHERBOARD Socket 478

Browse by processor

-- Select One -- ▼

IT7-MAx2



Intel 845E Based Pentium 4 ATX Mainboard
 Serial ATA, ATA133 RAID, 6 Channel Audio, IEEE 1394,
 USB 2.0
 SoftMenu™ Technology

Product Information

- [Overview](#)
- [Specifications](#)
- [News](#)
- [Awards](#)
- [Test Reports](#)

Support Information

- [FAQs](#)
- [BIOS](#)
- [Driver](#)

Specifications

- CPU**
- Supports Intel Pentium 4 Socket 478 processors with 400/533 MHz Front Side Bus
- Chipset**
- Intel 845E / ICH4
 - Supports Ultra DMA 33/66/100
 - Accelerated Graphics Port connector supports AGP 4X Interface (1.5V only)
- Memory**
- Three 184-pin DIMM sockets (unbuffered Non-ECC DIMM)
 - Supports 3 DIMM DDR 200/266 (Max. 2GB)
- Serial ATA**
- On board 2-Channel Serial ATA interface of 1.5 Gbps
- ATA133 RAID**
- High Point HPT374 IDE RAID controller
- Media XP (Optional)**
- Supports card reader function for Memory Stick™, Secure Digital™ and Type I/II CompactFlash™
 - Supports Wireless Remote Control and S/PDIF Out / Mc In / Headphone Out / USB 2.0 / IEEE 1394
- Audio**
- 6-Channel AC97 CODEC on board
- USB 2.0**
- 10 Ports USB 2.0
- IEEE 1394**
- 3 Ports IEEE 1394
- LAN**
- On board RTL8100B 10/100M PCI Fast Ethernet Controller
- System BIOS**
- SoftMenu™ Technology to set CPU parameters
 - Supports Plug-and-Play (PNP)
 - Supports Advanced Configuration Power Interface (ACPI)
- Internal I/O Connectors**
- 1 AGP slot, 4 PCI slots
 - Floppy Port supports up to 2.88MB
 - 2 x Ultra DMA 33/66/100 Connectors
 - 2 x Ultra DMA 33/66/100/133 Connectors (RAID)
 - 2 x Serial ATA 1.5Gbps Connectors
 - 1 x 6 Channel audio FPC pin header (for Media XP)
 - 2 x USB headers, 1 x IEEE 1394 header
 - 2 x CD-IN, 1 x IrDA
- Back Panel I/O**
- 1 x PS/2 Keyboard, 1 x PS/2 mouse
 - 4 x USB connectors
 - 2 x IEEE 1394 connectors
 - 1 x SPDIF Out connector
 - Audio connectors (Center/Sub, Surround Speaker)
 - Audio connectors (Front Speaker, Line-in, Mc-in)
 - 2 x USB, 1 x RJ-45 LAN Connector
- Miscellaneous**
- ATX form factor
 - Hardware monitoring - Including Fan speeds, Voltages, CPU and System environment temperature

- Supports Wake Up by LAN, Modem Ring, RTCAlarm
- Supports Keyboard and Mouse Power On
- Supports STR (Suspend to RAM)

Total Rows:5 Page:1/1

Model	Logo	Media	Country	Award	Date
IT7-MAX2		LinuxHardware.org	USA	Top Honors	2003/06/06
IT7-MAX2		LinuxHardware.org	USA	Works with Linux Certification	2003/06/06
IT7-MAX2		Tech-PC	UK	Rating: 95%	2002/10/25
IT7-MAX2		T-Break	USA	Rating: 9/10	2002/09/17
IT7-MAX2		Firing Squad	USA	Editor's Choice	2002/09/10

Copyright© 2006 Universal ABIT Co., Ltd. All rights reserved.
 Reproduction and distribution in any form without permission is strictly prohibited.
 The **abit** logo is a registered trademark of **abit**.