

abit Engineered

- | Press Center
- | BIOS Guide
- | CPU support
- | Downloads
- BIOS
- Drivers
- Utilities
- Manuals
- | FAQs
- | Awards
- | Contact Us
- | About Us
- R&D
- Customer Service
- Copyright info
- | HOME
- Newsletter Sign-Up
-
- Subscribe/ Unsubscribe
- Search
-
- Product
- FAQs
- News
- Award

MOTHERBOARD Socket 478

Browse by processor

-- Select One -- ▾

SG-71e



SIS 651/962L Based Pentium 4 mATX Mainboard
USB 2.0, ATA 133

Product Information

- [Overview](#)
- [Specifications](#)

Support Information

- [FAQs](#)
- [BIOS](#)
- [Driver](#)
- [Manual](#)

Specifications

CPU

- Supports Intel Pentium® 4 Socket478 processors with 400/533 MHz FSB

Chipset

- SIS 651/962L
- Accelerated Graphics Port connector supports AGP4X (1.5V)
- Supports H-Speed Universal Serial Bus (USB 2.0)

Graphic

- Integrated high performance 256-bit 3D engine and 2DAccelerator

Memory

- Two 184-pin DIMM sockets (Un-buffered Non-ECC DIMM)
- Supports 2 DIMM DDR200/266/333 (Max. 2GB)

Audio

- AC97 2 Ch Audio CODEC on board

LAN

- On board PCI Fast Ethernet Controller
- 10/100M Operation support ACPI

System BIOS

- Support BIOS Protect function adjust by BIOS
- Supports Plug-and-Play (PnP)
- Supports Advanced Configuration Power Interface (ACPI)
- Supports Desktop Management Interface (DMI)
- Write-Protect Anti-Virus function by AWARD BIOS

Internal I/O Connectors

- 1x AGP slot, 3 x PCI slots
- Floppy Port supports up to 2.88MB
- 2 x Ultra DMA 33/66/100/133 Connectors
- 2 x USB 2.0 headers
- 1 x CD-IN, 1 x AUX-IN
- 1 x IrDA

Back Panel I/O

- 1 x PS/2 Keyboard, 1 x PS/2 mouse
- 1 x Serial, 1 x Parallel, 1 x VGA Connector
- 2 x USB 2.0, 10/100MLAN Connector
- Audio connectors (Line-out, Line-in, Mc-in and Game Port)

Miscellaneous

- Micro ATX form factor
- Support STR (Suspend to RAM)
- Hardware Monitoring - Including Fan speed, Voltages, CPU and System temperature
- Keyboard and Mouse Power On