

**abit** *Engineered*

| P r e s s C e

| B I O S G u i

| C P U s u p p

| D o w n l o a

BIOS

Drivers

Utilities

Manuals

| F A Q s

| A w a r d s

| C o n t a c t

| A b o u t

R&D

Customer Service

Copyright info

| H O M E

Newsletter Sign-Up

Please enter a valid

Subscribe/ Unsubscribe

Search

Product

FAQs

News

Award

MOTHERBOARD Socket 478

Browse by processor

-- Select One -- ▾

**SG-72e**



SIS 661FX/964L Based Pentium 4  $\mu$ ATX Mainboard  
USB 2.0, ATA 133, Intel HT Technology

Product Image



Product Information

[Overview](#)

[Specifications](#)

[Test Reports](#)

Support Information

[FAQs](#)

[BIOS](#)

[Driver](#)

[Manual](#)

- Specifications**
- >> CPU**
- Supports Intel Pentium 4 Socket478 processors with 800/533/400 MHz FSB
  - Supports Intel Hyper-Threading Technology
- >> Chipset**
- SIS 661FX/964L
  - SIS MuTIOL 1G technology supports 1GB/s Multithread I/O Link
  - Supports DDR 400 Memory
  - Accelerated Graphics Port connector supports AGP 8X/4X
  - Supports Hi-Speed Universal Serial Bus (USB 2.0)
- >> Graphic**
- Integrated SIS Real256E GPU high performance 256-bit 3D engine and 2D Accelerator
- >> Memory**
- Two 184-pin DIMM sockets (Un-buffered Non-ECC DIMM)
  - Supports 2 DIMM DDR 266/333/400 (Max. 2GB)
- >> Audio**
- AC'97 6Ch Audio CODEC on board
- >> LAN**
- On board PCI Fast Ethernet Controller
  - 10/100M Operation support ACPI
- >> System BIOS**
- Support BIOS Protect function adjust by BIOS
  - Supports Plug-and-Play (PnP)
  - Supports Advanced Configuration Power Interface (ACPI)
  - Supports Desktop Management Interface (DMI)
  - Write-Protect Anti-Virus function by AWARD BIOS
- >> Internal I/O Connectors**
- 1 x AGP slot, 3 x PCI slots
  - Floppy Port supports up to 2.88MB
  - 2 x Ultra DMA 33/66/100/133 Connectors
  - 2 x USB 2.0 headers
  - 1 x CD-IN
- >> Back Panel I/O**
- 1 x PS/2 Keyboard, 1 x PS/2 mouse
  - 1 x Serial, 1 x Parallel, 1 x VGA Connector
  - 4 x USB 2.0, 10/100M LAN Connector
  - Audio connectors (Line-out, Line-in, Mic-in)
- >> Miscellaneous**
- Micro ATX form factor
  - Support STR (Suspend to RAM)
  - Hardware Monitoring - Including Fan speed, Voltages, CPU and System temperature
  - Keyboard and Mouse Power On

