


**abit Engineered™**

- Press Center
- BIOS Guide
- CPU support
- Download
- BIOS
- Drivers
- Utilities
- Manuals
- FAQs
- Awards
- Contact Us
- Abroad Us
- R&D
- Customer Service
- Copyright info
- HOME
- Newsletter Sign-Up
- Please enter a valid
- Subscribe/ Unsubscribe
- Search
- Product
- FAQs
- News
- Award


MOTHERBOARD Socket 939

Browse by processor -- Select One --

**AN8 SLI**



- Socket 939
- Nvidia® NF4 SLI
- 2GHz HT
- Dual DDR 400
- Nvidia SLI Tech.
- SATA 3G RAID
- NV GbE
- NV Firewall
- IEEE1394a
- ABIT µGuru™
- ABIT Silent OTES
- AudioMAX™



**Specifications**

- >> CPU**
- Supports AMD Socket 939 Athlon 64/64FX & [Athlon 64 X2 dual-core](#) Processors
  - With 2GHz system bus using Hyper Transport™ technology
  - Supports AMD CPU Cool 'n' Quiet Technology

- >> Chipset**
- NVIDIA NF4 SLI single chip
  - NVIDIA Gigabit Ethernet with NVIDIA Firewall
  - Supports NV SATA 3G RAID

- >> NVIDIA SLI Technology**
- Two PCI-Express X16 slots support NVIDIA Scalable Link Interface
  - Increase bandwidth of the PCI Express™ bus providing 60x the bandwidth of PCI

- >> Memory**
- Four 184-pin DIMM sockets
  - Supports dual channel DDR400 non-ECC un-buffered memory
  - Supports maximum memory capacity up to 8GB

- >> ABIT Engineered**
- ABIT µGuru™ Technology
  - ABIT Patented Silent OTES™ Technology\*
  - ABIT AudioMAX™ Technology
  - ABIT CPU ThermalGuard™ Technology

- >> NV SATA RAID**
- Serial ATA 3Gbps data transfer rate
  - Supports SATA RAID 0/1/0+1

- >> NV GbELAN**
- NVIDIA Gigabit Ethernet
  - NVIDIA Secure Networking Engine

- >> NV Firewall**
- Native NVIDIA Firewall

- >> IEEE1394**
- Support IEEE 1394 at 400 Mb/s transfer rate

- >> ABIT AudioMAX**
- High quality 7.1-channel Audio Card
  - Optical S/P DIF Input/Output
  - Supports auto jack sensing

- >> Internal I/O Connectors**
- 2 x PCI Express X16, 2 x PCI Express X1, 2 x PCI slots, 1 x AudioMAX
  - Floppy Port supports up to 2.88 MB
  - 2 x Ultra DMA 133/100/66/33 IDE Connectors
  - 4 x SATA 3G Connectors

**Product Information**

- [Specifications](#)
- [News](#)
- [Awards](#)
- [Test Reports](#)

**Support Information**

- [FAQs](#)
- [BIOS](#)
- [Driver](#)
- [Utility](#)
- [Manual](#)

**Compatibility Information**

- [CPU](#)

- 3 x USB headers, 1 x IEEE 1394 header

**>> Back Panel I/O**

- ABIT Patented Silent OTES™ Technology\*
- 1 x PS/2 Keyboard, 1 x PS/2 mouse
- 1 x IEEE 1394
- 4 x USB, 1 x RJ-45 LAN Connector

**>> Form Factor**

- ATX form factor 305 x 245mm

**>> Accessories**

- ABIT AudioMAX Card
- SLI Connector Bridge
- SLI Switch
- SATA cable x 4, ATA 100 IDE Cable x 1, FDD cable x 1, USB Bracket
- I/O shield x 1
- CD Title x 1, SATA Utility Disk x 1
- A5 standard User's Manual x 1, B5 multilingual Quick Installation Guide x 1
- Jumper Setting Label x 1

**>> Compatible Accessories**

- [Guru Panel™](#)

\*Patent No. M273189

Total Rows:7 Page:1/1

<a href="#">Model</a>	<a href="#">Logo</a>	<a href="#">Media</a>	<a href="#">Country</a>	<a href="#">Award</a>	<a href="#">Date</a>
<a href="#">AN8 SLI</a>		<a href="#">MKTech</a>	Belgium	<a href="#">Recommended</a>	2005/12/28
<a href="#">AN8 SLI</a>		<a href="#">AMDZone</a>	USA	<a href="#">Editor's Choice</a>	2005/12/13
<a href="#">AN8 SLI</a>		<a href="#">PC Modding</a>	Malaysia	Recommended	2005/12/01
<a href="#">AN8 SLI</a>		<a href="#">OCWorkbench</a>	Singapore	Recommended	2005/08/29
<a href="#">AN8 SLI</a>		<a href="#">Gaming Nexus</a>	USA	<a href="#">Editor's Choice</a>	2005/08/23
<a href="#">AN8 SLI</a>		<a href="#">Hardcoreware</a>	USA	<a href="#">I AM HARDWARE</a>	2005/08/09
<a href="#">AN8 SLI</a>		<a href="#">Motherboards.org</a>	USA	<a href="#">Editor's Choice</a>	2005/08/06

Copyright© 2006 Universal ABIT Co., Ltd. All rights reserved.  
 Reproduction and distribution in any form without permission is strictly prohibited.  
 The abit logo is a registered trademark of abit.