

abit Engineered™

- Press Center
- BIOS Guide
- CPU support
- Downloads
- BIOS
- Drivers
- Utilities
- Manuals
- FAQs
- Awards
- Contact Us
- Abilit
- R&D
- Customer Service
- Copyright info
- HOME
- Newsletter Sign-Up
- Please enter a valid
- Subscribe/ Unsubscribe
- Search
- Go
- Product
- FAQs
- News
- Award

MOTHERBOARD Socket 939

Browse by processor

-- Select One --

AV8-3rd Eye




- Socket 939
- VIA® K8T800 Pro
- Dual DDR400
- Gigabit LAN
- USB2.0
- SATA150 RAID
- IEEE 1394
- 6ch Audio
- ABIT µGuru™



Specifications

- >> CPU**
- Supports AMD Athlon™ 64 / Athlon™ 64 FX 939-pin & [Athlon 64 X2 dual-core](#) processor
 - 2000MHz system bus using Hyper Transport™ technology



- >> CPU Integrated Dual Channel Memory Controller**
- Four 184-pin DIMM sockets (Un-buffered Non-ECC DIMM)
 - Supports 2 DIMM Single Channel DDR 400/333/266 (Max. 2GB)
 - Supports 4 DIMM Dual Channel DDR 400/333/266 (Max. 8GB)

Product Information

- [Specifications](#)
- [News](#)
- [Awards](#)
- [Test Reports](#)

- >> Chipset**
- VIA K8T800 Pro/ VT8237 chipset
 - Supports Advanced Configuration and Power Management Interface (ACPI)
 - Accelerated Graphics Port connector supports AGP 8X/4X

Support Information

- [FAQs](#)
- [BIOS](#)
- [Driver](#)
- [Utility](#)
- [Manual](#)

- >> SATA 150 RAID**
- Supports SATA 150 MB/s RAID 0/1

Compatibility Information

- [CPU](#)

- >> GbELAN**
- On board Gigabit PCI Ethernet Controller
 - Operation support ACPI & Wake on LAN

- >> IEEE 1394**
- Supports 3 ports IEEE 1394 at 100/200/400 Mb/s transfer rate

- >> Audio**
- 6-Channel AC'97 CODEC on board
 - Professional digital audio interface supports optical S/P DIF In/Out

- >> ABIT Engineered**
- ABIT µGuru™ Technology
 - ABIT CPU ThermalGuard™ Technology

- >> ABIT Guru Clock inside (The 3rd Eye On Your PC)**
- Instant Overclocking & H/W Monitoring & PC On/Off
 - MSN/E-mail Notification
 - Large LCD Screen & Room Temperature Display

- >> Internal I/O Connectors**
- 1 x AGP 8X/4X slot
 - 5 x PCI slots
 - 1 x Floppy Port supports up to 2.88 MB
 - 2 x Ultra DMA 133/100/66/33 Connectors
 - 2 x SATA 150 Connectors
 - 2 x USB headers, 2 x IEEE1394 headers
 - 1 x FP-Audio header
 - 1 x CD-IN, 1 x AUX IN

- >> Back Panel I/O**
- 1 x PS/2 Keyboard, 1 x PS/2 Mouse
 - 1 x Serial, 1 x Parallel, 1 x S/P DIF Output, 1 x S/P DIF Input
 - 1 x Audio connector (Center/Subwoofer, Surround Speaker)
 - 1 x Audio connector (Line Out, Line-in, MIC-in)
 - 2 x USB, 1 x IEEE1394 Connector

- 2 x USB, 1 x RJ-45 LAN Connector

>> **Miscellaneous**

- ATX form factor (305x245mm)

>> **Compatible Accessories**

- [Guru Panel™](#)

Total Rows:3 Page:1/1

Model	Logo	Media	Country	Award	Date
AV8-3rd Eye		3DItalia-Multiplayer	Italy	'Best Hardware' Award	2004/12/28
AV8-3rd Eye		Overclockers	Poland	Recommendation	2004/10/14
AV8-3rd Eye		IN4	Poland	'Quality' and 'Best Buy'	2004/09/11

Copyright© 2006 Universal ABIT Co., Ltd. All rights reserved.
 Reproduction and distribution in any form without permission is strictly prohibited.
 The abit logo is a registered trademark of abit.