

abit Engineered™

- | P r e s s C e
- | B I O S G u i
- | C P U s u p p
- | D o w n l o a
- BIOS
- Drivers
- Utilities
- Manuals
- | F A Q s
- | A w a r d s
- | C o n t a c t
- | A b o u t
- R&D
- Customer Service
- Copyright info
- | H O M E
- Newsletter Sign-Up
- Please enter a valid
- Subscribe/ Unsubscribe
- Search
- Go
- Product
- FAQs
- News
- Award

MOTHERBOARD

Socket 939

Browse by processor

-- Select One --

Fatal1ty AN8 SLI



- Socket 939
- Nvidia® NF4 SLI
- 2GHz HT
- Dual DDR400
- Nvidia SLI Tech.
- NV SATA 3G RAID
- NV GbE
- NV Firewall
- IEEE 1394a
- ABIT µGuru™ 2003
- ABIT Silent OTES
- AudioMAX™
- Guru Panel

[What is µGuru™ Panel?](#)



Specifications

>> CPU

- Supports AMD Socket 939 Athlon 64/64FX & [Athlon 64 X2 dual-core](#) Processors
- With 2GHz system bus using Hyper Transport™ technology
- Supports AMD CPU Cool 'n' Quiet Technology

>> Chipset

- NVIDIA NF4 SLI single chip
- NVIDIA Gigabit Ethernet with NVIDIA Firewall
- Supports NV SATA 3G RAID

>> NVIDIA SLI Technology

- Two PCI-Express X16 slots support NVIDIA Scalable Link Interface
- Increase bandwidth of the PCI Express™ bus providing 60x the bandwidth of PCI

>> Memory

- Four 184-pin DIMM sockets
- Supports dual channel DDR400 non-ECC un-buffered memory
- Supports maximum memory capacity up to 8GB

>> ABT Engineered

- ABIT µGuru™ 2003 Technology
- ABIT Patented Silent OTES™ Technology*
- ABIT AudioMAX™ Technology
- ABIT CPU ThermalGuard™ Technology
- [ABIT Guru Panel™ Included](#)

>> NV SATA RAID

- Serial ATA 3Gbps data transfer rate
- Supports SATA RAID 0/1/0+1

>> NV GbELAN

- NVIDIA Gigabit Ethernet
- NVIDIA Secure Networking Engine

>> NV Firewall

- Native NVIDIA Firewall

>> IEEE1394

- Support IEEE 1394 at 400 Mb/s transfer rate

>> ABT AudioMAX

- High quality 7.1-channel Audio Card
- Optical S/P DIF Input/Output
- Supports auto jack sensing

>> Internal I/O Connectors

- 2 x PCI Express X16, 2 x PCI Express X1, 2 x PCI slots, 1 x

Product Information

[Specifications](#)

[News](#)

[Awards](#)

[Test Reports](#)

Support Information

[FAQs](#)

[BIOS](#)

[Driver](#)

[Utility](#)

[Manual](#)

Compatibility Information

[CPU](#)

- AudioMAX
- Floppy Port supports up to 2.88 MB
 - 2 x Ultra DMA 133/100/66/33 IDE Connectors
 - 4 x SATA 3G Connectors
 - 3 x USB headers, 1 x IEEE 1394 header

>> **Back Panel I/O**

- ABIT Patented Silent OTES™ Technology*
- 1 x PS/2 Keyboard, 1 x PS/2 mouse
- 1 x IEEE 1394
- 4 x USB, 1 x RJ-45 LAN Connector

>> **Form Factor**

- ATX form factor 305 x 245mm

>> **Accessories**

- OTES SLIstream
- Guru Panel
- ABIT AudioMAX Card
- SLI Connector Bridge
- SLI Switch
- SATA cable x 4, ATA 100 IDE Cable x 1, FDD cable x 1
- I/O shield x 1
- CD Title x 1, SATA Utility Disk x 1
- A5 standard User's Manual x 1, B5 multilingual Quick Installation Guide x 1
- Jumper Setting Label x 1

*Patent No. M273189

Total Rows:10 Page:1/1

Model	Logo	Media	Country	Award	Date
Fatal1ty AN8 SLI		Hot Hardware	USA	Heat Meter of 8.5	2006/01/16
Fatal1ty AN8 SLI		BYTE magazine	Turkey	The best Product of the year	2005/12/01
Fatal1ty AN8 SLI		OCPrices	UK	Elite Choice	2005/09/13
Fatal1ty AN8 SLI		The Games Machine	Italy	Best Buy	2005/09/08
Fatal1ty AN8 SLI		PC Perspective	USA	Gold	2005/08/19
Fatal1ty AN8 SLI		T-Break	Middle East	Editor's Choice	2005/08/09
Fatal1ty AN8 SLI		Tech Zone	Canada	Editor's Choice	2005/08/05
Fatal1ty AN8 SLI		GeForce	Italy	Must	2005/08/05
Fatal1ty AN8 SLI		HEXUS	UK	Recommended	2005/07/22
Fatal1ty AN8 SLI		TweakPC	Germany	TOP PRODUCT	2005/07/13

Copyright© 2006 Universal ABIT Co., Ltd. All rights reserved.
 Reproduction and distribution in any form without permission is strictly prohibited.
 The abit logo is a registered trademark of abit.