

**abit Engineered™**

- Press Center
- BIOS Guide
- CPU supports
- Downloads
- BIOS
- Drivers
- Utilities
- Manuals
- FAQs
- Awards
- Contact Us
- Abroad
- R&D
- Customer Service
- Copyright info
- HOME
- Newsletter Sign-Up
- Please enter a valid
- Subscribe/ Unsubscribe
- Search
- Go
- Product
- FAQs
- News
- Award

**MOTHERBOARD** Socket A

**Browse by processor**

-- Select One --

**NF7-S**



nForce 2 Chipset (K7), FSB 400, Dual DDR400, AGP 8X, Serial ATA, IEEE1394, USB2.0  
SoftMenu™ ABIT Engineered




**Product Information**

- [Overview](#)
- [Specifications](#)
- [News](#)
- [Awards](#)
- [Test Reports](#)

**Support Information**

- [FAQs](#)
- [BIOS](#)
- [Driver](#)
- [Utility](#)
- [Manual](#)

- Specifications**
- CPU**
- Ready for AMD400FSB Processors
  - Supports AMD-K7 / Athlon / Athlon XP/Barton FSB 200/266/333MHz FSB Processors
  - Supports AMD Sempron CPUs (Please update the latest BIOS version)
- Chipset**
- NVIDIA nForce™2 C18D chipset with MCP-T
  - Supports Advanced Configuration and Power Management Interface (ACPI)
  - Accelerated Graphics Port connector supports AGP 8X/4X (0.8V/1.5V)
- Memory**
- Three 184-pin DIMM sockets
  - Supports 3 DIMM DDR200/266/333 (Max. 3 GB)
  - Supports 2 DIMM DDR400 (Max. 2 GB)
- Serial ATA150 RAID**
- On board SATA 150 PCI Controller
  - Support 2 ports SATA 150 RAID 0/1
- Audio**
- 6-Channel AC97 CODEC on board
  - Professional digital audio interface supports optical S/PDIF Out
  - NVIDIA SoundStorm with real-time Dolby Digital 5.1 encoder
- IEEE 1394**
- Supports IEEE 1394a at 100/200/400 Mb/s transfer rate
- LAN**
- On board 10/100MLAN Physical layer interface
- ABIT Engineered**
- ABIT SoftMenu™ Technology
  - ABIT MaxFID™ Technology
  - ABIT SERILLEL™
  - ABIT CPU ThermalGuard™
- Internal I/O Connectors**
- 1 x AGP8X/4X, 5 x PCI slots
  - 1 x Floppy Port supports up to 2.88MB
  - 2 x Ultra DMA 33/66/100/133 Connectors
  - 2 x SATA 150 Connectors
  - 2 x USB 2.0 headers, 2 x IEEE1394 header
  - 2 x CD-IN
  - 1 x IrDA
- Back Panel I/O**
- 1 x PS/2 Keyboard, 1 x PS/2 mouse
  - 2 x Serial, 1 x Parallel
  - 1 x S/PDIF Out port
  - Audio connectors (Front Speaker, Line-in, Mic-in, Center/Sub, Surround Speaker)
  - 2 x USB 2.0, 1 x RJ-45 LAN Connector
- Miscellaneous**
- ATX form factor
  - Hardware monitoring - Including Fan speeds, Voltages, System environment temperature

Total Rows:8 Page:1/1

Model	Logo	Media	Country	Award	Date
				"Contest of	

<a href="#">NF7-S</a>		<a href="#">Systemcooling.net</a>	USA	<a href="#">"QUEST OF 2003"</a>	2004/01/15
<a href="#">NF7-S</a>		<a href="#">OCWorkbench</a>	Singapore	<a href="#">Reader's Choice</a>	2004/01/15
<a href="#">NF7-S</a>		<a href="#">Gruntville.com</a>	USA	<a href="#">Editor's Choice</a>	2003/09/11
<a href="#">NF7-S</a>		<a href="#">AMDZone</a>	USA	<a href="#">Score: 94</a>	2003/07/30
<a href="#">NF7-S</a>		<a href="#">OCAddiction</a>	USA	<a href="#">OCA Essential Hardware</a>	2003/06/27
<a href="#">NF7-S</a>		PCAction	Germany	<a href="#">Freistipp</a>	2003/04/15
<a href="#">NF7-S</a>		<a href="#">VRZone</a>	Singapore	<a href="#">Editor's Choice Silver</a>	2003/03/11
<a href="#">NF7-S</a>		<a href="#">TechZone</a>	USA	<a href="#">A+</a>	2003/02/21

Copyright© 2006 Universal ABIT Co., Ltd. All rights reserved.  
Reproduction and distribution in any form without permission is strictly prohibited.  
The abit logo is a registered trademark of abit.