



## Server WHQL Testing Services

### Enterprise Platforms and Services Division

# Intel® Server Board SE7520JR2SCSID2

---

## Server Test Submission (STS) Report

### For the Microsoft® Windows® Logo Program (WLP)

Rev 1.0

**November 22, 2004**

This report describes the Intel® SE7520JR2SCSID2 Server Platform Windows\* Logo Program test run conducted by Intel Enterprise Platforms and Services Division (EPSD).

#### **Purpose of this WLP Submission:**

System First Time submission for the Microsoft\* Designed for Windows Logo submission for the Intel® Server Board SE7520JR2SCSID2.

Submission Type:	Reason for test run	Check one
First Time Submission	Initial Microsoft Designed for Windows logo submission. New product submission.	<input checked="" type="checkbox"/>
System Update	Hardware update. (For example, update submission test run with new processor speeds.)	<input type="checkbox"/>
BIOS Update	BIOS and/or Firmware update. (For example, update submission test run with new BIOS to support additional processor speeds.)	<input type="checkbox"/>
OS Update	OS update. (For example, update submission test run to add Microsoft Designed for Windows Server 2003 logo to product.)	<input type="checkbox"/>

# Revision History and Disclaimers

---

Revision History		
Revision	Date	Comments
1.0	11/22/2004	Internal draft of the STS Report for Windows Server 2003 & Windows 2000 WLP Submission for Intel® Server Board SE7520JR2SCSID2only.

THIS TEST REPORT IS PROVIDED "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NONINFRINGEMENT FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION OR SAMPLE.

Information in this document is provided in connection with Intel® products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by the sale of Intel products. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, life saving, or life sustaining applications.

Intel retains the right to make changes to its test specifications at any time, without notice.

The hardware vendor remains solely responsible for the design, sale and functionality of its product, including any liability arising from product infringement or product warranty.

Intel, Pentium, Itanium and Xeon are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

\* Other names and brands may be claimed as the property of others.

Copyright © 2004, Intel Corporation. All rights reserved.

# Contents

---

<b>Revision History and Disclaimers .....</b>	<b>2</b>
<b>Introduction .....</b>	<b>4</b>
Overview of Contents.....	4
Terms and Definitions .....	4
<b>Server Board Submission Information.....</b>	<b>5</b>
Intel Server Board Submission Report: Completion of WLP.....	5
Submission Information .....	5
Submission ID.....	5
Submission Type .....	5
Product Category .....	5
Product Detail .....	5
General Product Information.....	5
Characterization (optional).....	5
Server Board Configuration Information .....	6
Processor.....	6
System Memory .....	6
Power Management.....	6
BIOS .....	6
Bus Types .....	7
Integrated Components .....	7
Onboard Integrated Devices and Drivers.....	7
Product Data for HCL: Completion of WLP.....	8
Product Data .....	8
<b>Hardware Compatibility Tests Used.....</b>	<b>9</b>
<b>Errata and Contingencies.....</b>	<b>10</b>
Submission Readme File.....	10
Testing Exceptions for Intel® Server SE7520JR2SCSID2 Windows 2000 Submission .....	11
Additional Information .....	11
Testing Exceptions for Intel® Server SE7520JR2SCSID2 Windows Server 2003.....	12
Additional Information .....	13
<b>Appendix A – Submission History.....</b>	<b>14</b>

# Introduction

---

This report provides an overview of the testing conducted on the Intel® Server Board SE7520JR2SCSID2 by Intel EPSD and provides details about this testing run.

## Overview of Contents

Section	Content
Introduction	Brief descriptions of the sections in the report. Table listing terms and definitions.
Server Product Submission Information	Submission information, ID # and final server board configuration upon completion of WLP including HW, Driver version, BIOS version, and Board AA number
HCT	All HCT's used during testing
Errata and Contingencies	All Microsoft* errata or contingencies used during testing

## Terms and Definitions

Term	Definitions
EPSD	Enterprise Platforms and Services Division
HCL	Windows Hardware Compatibility List. You can view the HCL at: <a href="http://www.microsoft.com/whdc/hcl/search.mspx">http://www.microsoft.com/whdc/hcl/search.mspx</a>
HCT	Hardware Compatibility Tests. For latest Server HCTs visit: <a href="http://www.microsoft.com/whdc/hwtest/system/default.mspx">http://www.microsoft.com/whdc/hwtest/system/default.mspx</a>
STS	Server Test Submission Report published by EPSD
WHDC	Windows* Hardware and Driver Central. Provides technical information, development and testing kits, newsletters and support information. <a href="http://www.microsoft.com/whdc/default.mspx">http://www.microsoft.com/whdc/default.mspx</a>
WHOS	Windows Hardware Online Service – Secure online web site used to submit products for logo qualification and review submission history. <a href="https://winqual.microsoft.com/">https://winqual.microsoft.com/</a>
WHQL	Windows* Hardware Qualification Lab. For more information visit the WHDC home page at: <a href="http://www.microsoft.com/whdc/default.mspx">http://www.microsoft.com/whdc/default.mspx</a>
WLP	Windows Logo Program. For further information see: <a href="http://www.microsoft.com/whdc/winlogo/default.mspx">http://www.microsoft.com/whdc/winlogo/default.mspx</a>
WTS	Workstation Test Submission Report published by EPSD

# Server Board Submission Information

---

## Intel Server Board Submission Report: Completion of WLP

Data in this section reflects system submission information at the time of WLP Update submission.

### Submission Information

Submission ID		
Submission ID / Master ID	911738	
Submission Type		
	Check Submission Type	Comments
First-Time Hardware and Driver Test Submission	<input checked="" type="checkbox"/>	
System Update Test Submission	<input type="checkbox"/>	
Product Category		
Hardware Category	PC System or Server	
Operating System family	Windows Server 2003 and Windows 2000 families	
Product Detail		
General Product Information		
Equipment Type	Server	
Primary Target Market	Business/Corporate	
Compliance	All applicable requirements	
Characterization (optional)		
	Check appropriate options	Comments
Web Server	<input checked="" type="checkbox"/>	
SQL Database Server	<input checked="" type="checkbox"/>	
File Server	<input checked="" type="checkbox"/>	

## Server Board Configuration Information

Processor	
Quantity	2 (physical processors installed)
Front Side Bus Speed	800 MHz
Family/Model	The Intel Server Board SE7520JR2SCSID2 supports either one or two Intel® Xeon™ processors with either 1MB L2 cache or 2MB L2 cache
Speed	2.8MHz, 3.0MHz, 3.2MHz, 3.4MHz, 3.6MHz
System Memory	
Amount Installed	8 GB
Memory Type	Registered ECC DDR2 400MHz
Power Management	
ACPI Sleep States (S1, S2, S3, S4)	S1, S4
Server Board Product	
System uses logo'd motherboard	NO (Server boards are <u>NOT</u> eligible for logo under the Microsoft* Motherboard logo program)
Board AA #/Fab	PBA C53661-301
Board Manufacturer	Intel Corporation
Board Model	Intel® Server Board SE7520JR2SCSID2
Northbridge* Chipset Manufacturer	Intel Corporation
Northbridge Chipset Model	Intel E7520 Chipset
Southbridge* Chipset Manufacturer	Intel Corporation
Southbridge Chipset Model	Intel E7520 Chipset
BIOS	
BIOS Manufacturer	AMI*
BIOS Version	P04.4
BIOS Date	10/20/2004
BIOS URL (For Updates)	<a href="http://support.intel.com/support/motherboards/server/SE7520JR2/">http://support.intel.com/support/motherboards/server/SE7520JR2/</a>

Bus Types			
	Check all that Apply		Check all that Apply
PS/2	<input checked="" type="checkbox"/>	AGP*	<input type="checkbox"/>
1394	<input type="checkbox"/>	PCCard* (16-bit)	<input type="checkbox"/>
CF (Compact Flash)	<input type="checkbox"/>	CardBus* (32-bit)	<input type="checkbox"/>
PCI	<input checked="" type="checkbox"/>	USB	<input type="checkbox"/>
Mini-PCI	<input type="checkbox"/>	USB 2.0	<input checked="" type="checkbox"/>
AMR	<input type="checkbox"/>	InfiniBand*	<input type="checkbox"/>
ACR	<input type="checkbox"/>	Bluetooth*	<input type="checkbox"/>
COM (Serial)	<input checked="" type="checkbox"/>	PCI Express	<input checked="" type="checkbox"/>
Integrated Components			
	Check all that Apply		Check all that Apply
Audio	<input type="checkbox"/>	Display	<input checked="" type="checkbox"/>
IDE	<input checked="" type="checkbox"/>	Networking	<input checked="" type="checkbox"/>
SCSI	<input checked="" type="checkbox"/>	RAID	<input checked="" type="checkbox"/>
Modem	<input type="checkbox"/>	Bluetooth*	<input type="checkbox"/>

## Onboard Integrated Devices and Drivers

Data in this section reflects system configuration at the time of WLP submission. The latest drivers for the Intel® Server Board SE7520JR2SCSID2 are available for download at:

<http://support.intel.com/support/motherboards/server/SE7520JR2SCSID2/>

Technology	OS	Version
<b>LAN</b> 2 X Intel 82546GB (Anvik-II) / PRO1000	<b>Windows* 2000</b>	v7.4.19
	<b>Windows Server 2003</b>	v7.4.19
<b>Display</b> ATI* Rage* XL SVGA PCI video controller with 8 MB of video memory	<b>Windows 2000</b>	Embedded
	<b>Windows Server 2003</b>	Embedded
<b>Serial RAID ATA</b> <b>ICH5-R-ESB6300</b> Can be configured as either a RAID 1 or 0	<b>Windows 2000</b>	4.1.0804.2004
	<b>Windows Server 2003</b>	4.1.0804.2004

**Product Data for HCL: Completion of WLP**

Data in this section reflects product data for HCL at time of WLP submission.

<b>Product Data</b>		
Product Name	Intel® Server Board SE7520JR2SCSID2	
Additional Product Names		
<b>Supported Platforms</b>		
	<b>Check Tested</b>	<b>Comments</b>
Windows 2000 Server	<input checked="" type="checkbox"/>	
Windows 2000 Advanced Server	<input checked="" type="checkbox"/>	
Windows Server 2003, Web Edition	<input checked="" type="checkbox"/>	
Windows Server 2003, Standard Edition	<input checked="" type="checkbox"/>	
Windows Server 2003, Enterprise Edition	<input checked="" type="checkbox"/>	



# Hardware Compatibility Tests Used

Microsoft\* Windows Hardware Driver Central Server Testing Home Page:

<http://www.microsoft.com/whdc/hwtest/system/default.mspx>.

Please check this website regularly for test kit updates.

Operating Systems	Notes	Hardware Compatibility Tests (HCT)
Windows* 2000	HCT 9.502 Test Procedures for Systems, Servers and Cluster Servers (Windows 2000)  <a href="http://download.microsoft.com/download/whistler/Docs/Docs/W982KMeXP/EN-US/HCT9502_Systems.exe">http://download.microsoft.com/download/whistler/Docs/Docs/W982KMeXP/EN-US/HCT9502_Systems.exe</a>	HCT 9.502 Test Kit (Windows 2000) (35.4 MB)  <a href="http://download.microsoft.com/download/whistler/Tools/Tools/W98NT42KMeXP/EN-US/HCT9502UPD.EXE">http://download.microsoft.com/download/whistler/Tools/Tools/W98NT42KMeXP/EN-US/HCT9502UPD.EXE</a>
	Logo'd Components Index Full Install	Logo'd Components Index Full Install (~9.8 MB)  <a href="http://download.microsoft.com/download/whistler/Install/20.0/W982KMeXP/EN-US/logoidx.exe">http://download.microsoft.com/download/whistler/Install/20.0/W982KMeXP/EN-US/logoidx.exe</a>
	391 NDIS Intermediate Drivers Instructions  <a href="http://download.microsoft.com/download/whistler/Install/20.1/W982KMeXP/EN-US/NDISIntermedDriver.exe">http://download.microsoft.com/download/whistler/Install/20.1/W982KMeXP/EN-US/NDISIntermedDriver.exe</a>	Beta NDIS Test Update (ndt391.exe) (2MB)  <a href="http://download.microsoft.com/download/whistler/Install/12.2/W982KMeXP/EN-US/ndt391.exe">http://download.microsoft.com/download/whistler/Install/12.2/W982KMeXP/EN-US/ndt391.exe</a>
	386 NDIS Intermediate Drivers Instructions  <a href="http://download.microsoft.com/download/whistler/Install/20.1/W982KMeXP/EN-US/NDISIntermedDriver.exe">http://download.microsoft.com/download/whistler/Install/20.1/W982KMeXP/EN-US/NDISIntermedDriver.exe</a>	NDIS Test Update for Windows 98 SE, Windows Me, and Windows 2000 (ndt386.exe) (2.02MB)  <a href="http://download.microsoft.com/download/whistler/Install/12.2/W982KMeXP/EN-US/ndt386.exe">http://download.microsoft.com/download/whistler/Install/12.2/W982KMeXP/EN-US/ndt386.exe</a>
Windows Server 2003	HCT 11.2 Test Procedures and Readme files for Windows XP SP1 and Windows Server 2003 (4.95MB)  <a href="http://www.microsoft.com/whdc/hwtest/search/details.aspx?ID=725">http://www.microsoft.com/whdc/hwtest/search/details.aspx?ID=725</a>	HCT 11.2 (Windows XP SP1 and Windows Server 2003) Test Kit (4.95MB)  <a href="http://www.microsoft.com/whdc/hwtest/search/details.aspx?ID=724">http://www.microsoft.com/whdc/hwtest/search/details.aspx?ID=724</a>
	Logo'd Components Index Full Install	Logo'd Components Index Full Install (~9.8 MB)  <a href="http://download.microsoft.com/download/whistler/Install/20.0/W982KMeXP/EN-US/logoidx.exe">http://download.microsoft.com/download/whistler/Install/20.0/W982KMeXP/EN-US/logoidx.exe</a>

# Errata and Contingencies

Microsoft\*System HCT Errata list is available at:

<http://www.microsoft.com/whdc/hwtest/search/results.aspx?type=errata&key=system&kit=-1>

Operating System	Identification Number	Title
Windows* 2000	298	PCI Power Management Register Interface Test: False Failure
Windows 2000	372	ACPI System test fails systems that support ACPI table version 1.0 or greater
Windows Server 2003	610	Intel ICHx Contingency
Windows 2000	702	Audio tests are not required for servers that do not implement audio devices
Windows 2000	719	DVD test cannot be run on systems without a DVD drive
Windows 2000	722	PCI 2.2 Compliance test and PCI 2.1 (Cards) test might fail test systems with ATA/ATAPI controllers
Windows Server 2003	772	LAN Device Wake test is not required on network devices in mobile systems, multifunction, broadband, LAN emulation, wireless LAN, server LAN, or bus-powered USB network devices
Windows 2000	826	PCI 2.1 Compliance test, PCI 2.1 Cards test, PCI 2.2 Compliance test, and CardBus Bridge Register test fail on devices that are PCI 2.3-compliant
Windows Server 2003	860	Enable/Disable – Device I/O test fails on USB 2.0 host controllers
Windows Server 2003	901	The ACPI Verifier test fails the E820 table when the system memory controller is a child of the PCI Bus
Windows Server 2003	1012	Enable/Disable - Device I/O test false-fails because of LPT port errors
Windows 2000	1182	ACPI Sleep test conflicts with Windows 2000 Service Pack 4

## Submission Readme File

Effective May 1, 2002, the new Microsoft standardized Readme form will be required for all hardware submissions that include any of the following testing exceptions:

- Test failures
- Tests not run
- Missing test logs
- Inconclusive test results

All testing exceptions must be identified with a valid Errata ID, Incident ID, or Contingency ID provided by WHQL. The new Microsoft standardized Readme file is available for download at:

<http://download.microsoft.com/download/whistler/install/1.0/w98nt42kmexp/en-us/readme.exe>

## **Testing Exceptions for Intel® Server Board SE7520JR2SCSID2 Windows 2000 Submission**

Data in this section reflects product data and test exceptions listed in section 2 of the Intel® Server Board SE7520JR2SCSID2 Readme file at time of WLP First-Time submission ID Number 911738.

### **Additional Information**

No additional information entered in section 3 of the Intel® Server Board SE7520JR2SCSID2 Readme file at time of WLP submission ID 911738.

**Windows 2000 logs are no longer required. Windows 2000 receives a ‘Supported’ status when submitted with a successful Windows 20003 submission.**

### Testing Exceptions for Intel® Server Board SE7520JR2SCSID2 Windows Server 2003

Data in this section reflects product data and test exceptions listed in section 2 of the Intel® Server Board SE7520JR2SCSID2 Readme file at time of WLP First-Time submission ID Number 911738.

Operating system (Windows XP, Windows 2000, etc.)	Failure type (Contingency, Errata, Incident)	ID number
Windows 2003 Enterprise Edition	Errata	860
<b>Failing test name</b>	Enable/Disable - Device I/O	
<b>Applicable error message</b> (Type <b>N/A</b> if the error message or failing text is excessive or if there is no text)	Variation 2: Starting test 4 PCI\VEN_8086&DEV_24D2&SUBSYS_10798086&REV_02\3&267A616A&0&E8   ID=PCI\VEN_8086&DEV_24D2&SUBSYS_10798086&REV_02\3&267A616A&0&E8  Friendly Name=(null)  Status=25175040 Prob=22   Status=DN_HAS_PROBLEM, DN_DISABLEABLE, DN_NT_ENUMERATOR, DN_NT_DRIVER,  Prob=CM_PROB_DISABLED  DevDesc=Intel(R) 82801EB USB Universal Host Controller - 24D2  Test Interface=(null)  PnP Interface=\\?\PCI#VEN_8086&DEV_24D2&SUBSYS_10798086&REV_02#3&267a616a&0&E8#{3abf6f2d-71c4-462a-8a92-1e6861e6af27}    TEST 4 :FAIL	
<b>Additional information</b> (for example, test system in a multiple system configuration)		

<b>Operating system</b> (Windows XP, Windows 2000, etc.)	<b>Failure type</b> (Contingency, Errata, Incident)	<b>ID number</b>
Windows 2003 Enterprise Edition	Errata	670
<b>Failing test name</b>	PCI Pre-OS Tests: PCI Configuration Header Dump test; <b>Pcidump.log</b> PCI Power Management Register Interface test; <b>Pcicap.log</b> Subsystem ID and Subsystem Vendor ID test; <b>Pcsid.log</b> PCI Test Adapter Diagnostic test; <b>Pmdiag.log</b> PME# Signal Routing test; <b>Pcipme1.log</b> PME# Signal Routing - Simultaneous test; <b>Pcipme2.log</b> PCI 3.3 Volt Auxiliary Power Load test; <b>Pcivaux.log</b> System Wake Up test; <b>Pciwake.log</b> PCI Voltage Requirement test; <b>Pcivolt.log</b> PCI Voltage Requirement - 3.3 Vaux test; <b>Pcivoltz.log</b> S3 Compliance test; <b>S3test.log</b>	
<b>Applicable error message</b> (Type <b>N/A</b> if the error message or failing text is excessive or if there is no text)		
<b>Additional information</b> (for example, test system in a multiple system configuration)	PCI Pre-OS tests that use FoxFire cards are no longer required	

<b>Operating system</b> (Windows XP, Windows 2000, etc.)	<b>Failure type</b> (Contingency, Errata, Incident)	<b>ID number</b>
Windows 2003 Enterprise Edition	Errata	901
<b>Failing test name</b>	ACPI Verifier	
<b>Applicable error message</b> (Type <b>N/A</b> if the error message or failing text is excessive or if there is no text)	The memory range specified is in conflict with the system's E820 table.   The E820 table says that this memory range is in the AcpiAddressRangeMemory range   which is conflicting with the requested memory range which is   between 0x0 - 0x9d800	
<b>Additional information</b> (for example, test system in a multiple system configuration)		

### Additional Information

There is an issue with the LSI Ultra 320 SCSI controller where it will exceed the time allowed by the test kit to cycle through the ACPI sleep states causing both the ACPI Extended and ACPI Varied tests to fail. Microsoft was contacted regarding this issue and stated it was okay to modify the .psf files to increase the time for the system to cycle through the sleep states. Please refer to Incident ID #1978.

## Appendix A – Submission History

Microsoft “Designed for Windows\*” logo submission history for the Intel® Server SE7520JR2SCSID2:

Submission ID	Type	Date	OS Qualified	Processor Speeds	Board Revision	BIOS Version
911738	First-Time	11/22/2004	Windows 2003 Windows 2000 (Supported status only)	2.8MHz, 3.0MHz, 3.2MHz, 3.4MHz, 3.6MHz	PBA C53661- 301	P04.4 .10/20/2004