Chenbro
RM118xx

www.chenbro.com.tw

Chassis Configuration Intel® Server Board SE7501CW2
Tested Chassis List Based On Mechanical and Thermal
Regression Testing of Chassis Posted on Server Board
SE7500CW2 and SHG2 Reference Lists
Model tested: RM118XX
Blowers (qty x size): 3 x 97mm Delta* BFB1012H
Hard drives: 2 x Seagate * ST318406LC
Processor: Two 2.4Ghz Intel ® Xeon ™ processors
Memory: 6 X Samsung* 128M DDR200 DIMM
M383L1713BTI-CA0
Power Supply: EMACS* 400W P1M-6400P
Additional Information: Validated to 2.4Ghz maximum
* Third party names and brands are the property of their respective owners.

**Note: Modifications to the tested configuration may cause
variations in actual performance.**

Product Information

Model#: RM118xx

Size: (DxWxH in): 25.8" x 17" x 1.72"

Size: (DxWxH mm): 655 x 430 x 43.5

5.25" Bays: 1

3.50" Bays: 2 IDE HDD bays

Cooling: 3x 97mm blowers

Power Supply: 400W

Other Information: Custom copper base Skiving CPU heat sinks included standard

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

List of Intel®
Server Boxed Boards
Mechanically Compatible with:
> **SHG2, SE7500CW2 & SE7501CW2**

Thermally Compatible with:
> **SHG2, SE7500CW2 & SE7501CW2**