



4U Rack RS 4100i

www.cidesign.com



Product Information

Model#: RS 4100i

Size: (LxWxH in): 24 x 19 x 6.97

Size: (LxWxH mm): 609.6 x 482.6 x 177.0

5.25" Bays: 5

3.50" Bays: 5 x SCA or removable IDE

Fans: Four 80mm std, Two 80mm optional

Power Supply: 2+1 Redundant

Other Information: Optional Slimline CD-Rom/FDD kit

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

Additional Information

Associated Model #s: Rack Server Series

Options: Fixed IDE, Removable IDE, hot swap SCSI

Chassis Configuration As tested with Intel Server board SE7505VB2

Model tested: RS 4100i

Fans (qty x size): 4 Minebea* 80mm 3110GL-B4W-B54, 2 Sunon* 80mm KD1208PT B2-6, 2 60mm Processor fans

Hard drives: 3 x Seagate* SCSI ST318406LC

Processor: 2 x Intel© 2.8 GHz Xeon™

Memory: 4 x Samsung* 128M DDR266 DIMM M386L1713BTI-CA0

Power Supply: EMACS* 460W MR3-6460P

Additional Information: CD Rom and Floppy drive

Note: Modifications to the tested configuration may cause variations in actual performance.

List of Intel

Real Server Boxed Boards

Mechanically Compatible with:

SE7505VB2

Thermally Compatible with:

SE7505VB2

* Third party names and brands are the property of their respective owners.