

Save and Exit Setup

ROM PCI/ISA BIOS (2A5L7F09) CMOS SETUP UTILITY AWARD SOFTWARE, INC.	
STANDARD CMOS SETUP	SUPERVISOR PASSWORD
BIOS FEATURES SETUP	USER PASSWORD
CHIPSET FEATURES SETUP	IDE HDD AUTO DETECTION
POWER MANAGEMENT SETUP	SAVE & EXIT SETUP
PCI CONFIGURATION	SAVE & EXIT SETUP
LOAD BIOS	SAVE to CMOS and EXIT (Y/N)? Y <input type="checkbox"/>
LOAD SETUP DEFAULTS	
ESC : Quit	
F10 : Save & Exit Setup	
SAVE DATA TO CMOS and EXIT SETUP	

After you have made changes under Setup, press <Esc> to return to the main menu. Move cursor to "Save and Exit Setup" or press "F10" and then press "Y" to change the CMOS Setup. If you did not change anything, press <Esc> again or move cursor to "Exit Without Saving" and press "Y" to retain the Setup settings. As you select this feature, the following message will appear at the center of the screen to allow you to save data to CMOS and exit the setup utility.

SAVE to CMOS and EXIT (Y/N)?

Exit Without Saving

As you select this feature, the following message will appear at the center of the screen to allow you to save data to CMOS and exit the setup utility.

Quit Without Saving (Y/N)?

→ **NOTE : Default values of the various Setup items on this chapter may not necessarily be the same ones shown on your screen.**