



In Win IW-R2000

www.in-win.com

Product Information

Model# IW-R2000

**Size (LxWxH inches/mm) 8 5/8 x 17 9/16 x 22 1/7 /
572 x 220 x 449**

5.25" Bays: 3

3.50" Bays (internal/external): 1/6

Fans: 1-12 cm , 2-8cm

Power Supply : Delta RPS-600C (337W Redundant)

**Other Information: System Lock, Intrusion detect,
Support UW/U2W SCSI, SE/LVD, SAF-TE, SMART, SES
Management, Level 4 Hot Plug, Add-on Card Lock,
SECC Japan Steel, Folded Edge, and Temperature
Alarm**

**Note: The above information is provided by the chassis
manufacturer and is the sole responsibility of the manufacturer.
Intel assumes no responsibility for any inaccuracies in this data or
any changes made by the manufacturer.**

Additional Information

Associated Model #s:

Options: Hot swap drives, power supply selection

Chassis Configuration (as tested with Intel's L440GX+ Server Board)

Model tested: IW-R2000

Fans: 2 x 80mm, 1 x 120 mm

Hard drives: 3 x Seagate* ST39102LC Cheetah*

Processor: 2 x 850MHz Pentium® III

Memory: 512 MB

Power Supply: Delta RPS-600C (337 Redundant HS)

RAID: Intel, BOXSRCU21

Additional Information:

*** Third Party names and brands are the property of the respective owner.**

**Note: Modifications to the tested configuration may cause
variations in actual performance.**

List of Intel

Real Server Boxed Boards

Mechanically Compatible with:

L440GX+ (850 MHz)

Thermally Compatible with:

L440GX+ (850 MHz)

CE Testing Performed with: